



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : LMM-6000 METAL MARKING AEROSOL SPRAY  
Product code : LMM-6000AER.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Ceramic covering that will undergo heat treatment on glass and ceramics.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : GRAVOTECH MARKING SAS.  
Address : 56, avenue Jean Jaurès.10600.La Chapelle Saint Luc.France.  
Telephone : +33 (0)3 25 41 65 65. Fax : +33 (0)3 25 79 04 25.  
e-mail : [info@gravograph.fr](mailto:info@gravograph.fr)  
<http://www.gravograph.com>

#### 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable aerosol, Category 1 (Flam. Aerosol 1, H222).  
Eye irritation, Category 2 (Eye Irrit. 2, H319).  
Carcinogenicity, Category 2 (Carc. 2, H351).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).  
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

##### In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Extremely flammable (F+, R 12).  
Eye irritation (Xi, R 36).  
Irritant for the respiratory tract (Xi, R 37).  
Category 3 carcinogen (Xn, R 40 Carc. Cat. 3).  
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

Mixture for aerosol application.

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

GHS08

GHS02

Signal Word :

DANGER

Product identifiers :

042-001-00-9

MOLYBDENUM TRIOXIDE

Hazard statements :

H222

Extremely flammable aerosol.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

H351

Suspected of causing cancer .

## Precautionary statements - Prevention :

- P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264 Wash hands thoroughly after handling.  
 P281 Use personal protective equipment as required.

## Precautionary statements - Response :

- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P337 + P313 If eye irritation persists: Get medical advice/attention.

## Precautionary statements - Storage :

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.

## Precautionary statements - Disposal :

- P501 Dispose of contents/container at a disposal facility in accordance with local regulations.

**2.3. Other hazards**

No data available.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.1. Substances**

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006.

**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 042-001-00-9 CAS: 1313-27-5 EC: 215-204-7  MOLYBDENUM TRIOXIDE	GHS08, GHS07 Wng Carc. 2, H351 Eye Irrit. 2, H319 STOT SE 3, H335	Xn Carc. Cat. 3;R40 Xi;R36/37		25 <= x % < 50
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43  ETHANOL	GHS02 Dgr Flam. Liq. 2, H225	F F;R11		25 <= x % < 50
CAS: 12001-26-2  MICA				10 <= x % < 25
INDEX: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9  PROPANE	GHS02, GHS04 Dgr Flam. Gas 1, H220	F+ F+;R12		2.5 <= x % < 10
CAS: 13718-26-8 EC: 237-272-7  SODIUM METAVANADATE	GHS06 Dgr Acute Tox. 3, H301 Acute Tox. 3, H331	T T;R23/25		1 <= x % < 2.5
CAS: 577-11-7 EC: 209-406-4  DOCUSATE SODIUM	GHS07 Wng Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	Xi Xi;R36/38 R52/53		1 <= x % < 2.5

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.  
NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.  
If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.  
If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

#### In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.  
If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.  
Keep the person exposed at rest. Do not force vomiting.  
Seek medical attention, showing the label.  
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.  
Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.  
Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non fire-fighters

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.  
Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilled, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### **For fire-fighters**

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

#### **6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

#### **6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

#### **6.4. Reference to other sections**

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### **7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### **Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### **Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

#### **7.2. Conditions for safe storage, including any incompatibilities**

No data available.

#### **Storage**

Keep the container tightly closed in a dry, well-ventilated place

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

#### **Packaging**

Always keep in packaging made of an identical material to the original.

#### **7.3. Specific end use(s)**

No data available.

## **SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
12001-26-2	3 mg/m <sup>3</sup>	-	-	-	R
74-98-6	1000 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
64-17-5	500 ml/m <sup>3</sup>	960 mg/m <sup>3</sup>	2(II)	DFG. Y
74-98-6	1000 ml/m <sup>3</sup>	1800 mg/m <sup>3</sup>	4(II)	DFG

- Belgium (Order of 19/05/2009, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
12001-26-2	3 mg/m <sup>3</sup>	-	-	-	-

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84

- Switzerland (SUVA 2009) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Temps :	RSB :
64-17-5	960	500	1920	1000	4x15	-
12001-26-2	3a	-	-	-	-	-
74-98-6	1800	1000	7200	4000	4x15	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm	-	-	-	-
12001-26-2	10 mg/m <sup>3</sup>	-	-	-	TI

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state :	fluid liquid.
	spray.
Colour:	White.

#### Important health, safety and environmental information

pH :	Not relevant.
Flash point interval :	not relevant.
Explosive properties, lower explosivity limit (%) :	2.1
Explosive properties, upper explosivity limit (%) :	19.0
Vapour pressure :	Below 110 kPa (1.10 bar).
Density :	> 1
Water solubility :	Insoluble.
Chemical combustion heat :	not specified.
Inflammation time :	not specified.
Deflagration density :	not specified.
Inflammation distance :	not specified.
Flame height :	not specified.
Flame duration :	not specified.

### 9.2. Other information

No data available.

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

### 10.5. Incompatible materials

Keep away from :

- oxidising agents

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.  
Splashes in the eyes may cause irritation and reversible damage  
Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.  
Suspected human carcinogen.

#### 11.1.1. Substances

##### Acute toxicity :

ETHANOL (CAS: 64-17-5)

Oral route : DL50 = 6200 mg/kg  
Species : Rat

Dermal route : DL50 > 20000 mg/kg  
Species : Rabbit

Inhalation route : CL50 > 8000 mg/l  
Species : Rat

#### 11.1.2. Mixture

No toxicological data available for the mixture.

##### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.1. Substances

Substances classified as category 1 acute toxicity :

ETHANOL (CAS: 64-17-5)

Fish toxicity : Duration of exposure : 48 h  
CL50 = 8140 mg/l

Crustacean toxicity : Duration of exposure : 48 h  
CE50 > 9268 mg/l

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

##### German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

##### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

##### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2011 - IMDG 2010 - ICAO/IATA 2012).

### 14.1. UN number

1950

### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### 14.3. Transport hazard class(es)

- Classification :



2.1

### 14.4. Packing group

-

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	2.1	SP63	-	SP277	F-D,S-U	63 190 277 327 959	E0			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Particular provisions :

No data available.

#### - German regulations concerning the classification of hazards for water (WGK) :

Germany : WGK 2 (VwVwS vom 27/07/2005, KBws)

### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :





Harmful



Extremely flammable

Contains :  
042-001-00-9 MOLYBDENUM TRIOXIDE

Risk phrase :  
R 36/37 Irritating to eyes and respiratory system.  
R 12 Extremely flammable.  
R 40 Limited evidence of a carcinogenic effect.

Safety phrase :  
S 16 Keep away from sources of ignition - No smoking.  
S 23 Do not breathe spray.  
S 36/37 Wear suitable protective clothing and gloves.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.  
Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S 60 This material and its container must be disposed of as hazardous waste.

**Title for H, EUH and R indications mentioned in section 3 :**

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer .
H412	Harmful to aquatic life with long lasting effects.
R 11	Highly flammable.
R 12	Extremely flammable.
R 23/25	Toxic by inhalation and if swallowed.
R 36/37	Irritating to eyes and respiratory system.
R 36/38	Irritating to eyes and skin.
R 40.C3	Limited evidence of a carcinogenic effect.
R 52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.  
IMDG : International Maritime Dangerous Goods.  
IATA : International Air Transport Association.  
ICAO : International Civil Aviation Organisation  
RID : Regulations concerning the International carriage of Dangerous goods by rail.  
WGK : Wassergefährdungsklasse (Water Hazard Class).  
GHS02 : Flame  
GHS07 : Exclamation mark  
GHS08 : Health hazard